



PTFE Rundstäbe extrudiert - Standardabmessungen

Durchmesser, mm		Länge, mm
Wert	Toleranz	
Extrudierte Rundstäbe		
4, 5, 6	0 ~ + 0,48	max. 3000
7, 8, 9	0 ~ + 0,58	max. 3.000
10, 12, 13, 15, 16	0 ~ +1,10	max. 3.000
17	0 ~ + 1,10	max. 2.000
18	0 ~ +1,10	max. 3.000
20	0 ~ + 1,30	max. 3.000
23	0 ~ + 1,40	max. 2.000
25	0 ~ + 1,30	max. 3.000
27	0 ~ + 1,60	max. 2.000
28	0 ~ + 1,70	max. 2.000
30	0 ~ + 1,30	max. 3.000
32	0 ~ + 1,90	max. 2.000
35	0 ~ + 1,60	max. 3.000
38	0 ~ + 2,30	max. 2.000
40	0 ~ + 1,60	max. 3.000
44	0 ~ + 2,60	max. 2000



45	0 ~ + 1,60	max. 3.000
46	0 ~ + 2,90	max. 2.000
50	0 ~ + 1,60	max. 3.000
55, 60, 65	0 ~ + 2,50	max. 3.000
68	0 ~ + 4,00	max. 2.000
70, 75, 80, 85	0 ~ + 2,50	max. 3.000
88	0 ~ + 5,20	max. 2.000
90, 95, 100	0 ~ + 2,50	max. 3.000
110, 120, 130, 140 ,150	0 ~ + 2,50	max. 3.000
180, 200	0 ~ + 3,00	max. 3.000

Nicht aufgeführte Abmessungen auf Anfrage