



PTFE Rundstäbe extrudiert - Standardabmessungen

Durchmesser, mm		Länge, mm
Wert	Toleranz	
Extrudierte Rundstäbe		
4, 5, 6	0 ~ +0,48	max. 3000
7, 8, 9	0 ~ +0,58	max. 3000
10, 12, 13, 15, 16, 18	0 ~ +1,10	max. 3000
17	0 ~ +1,10	max. 2000
20, 25, 30	0 ~ +1,30	max. 3000
23	0 ~ +1,40	max. 2000
27	0 ~ +1,60	max. 2000
28	0 ~ +1,70	max. 2000
32	0 ~ +1,90	max. 2000
35, 40, 45, 50	0 ~ +1,60	max. 3000
38	0 ~ +2,30	max. 2000
44	0 ~ +2,6	max. 2000
46	0 ~ +2,90	max. 2000
55, 60, 65, 70, 75, 80, 85, 90, 95, 100	0 ~ +2,50	max. 3000
68	0 ~ +4,00	max. 2000
88	0 ~ +5,20	max. 2000



110, 120, 130, 140, 150	0 ~ +2,50	max. 3000
180, 200	0 ~ +3,00	max. 3000
38	0 ~ +2,30	max. 2000
44	0 ~ +2,6	max. 2000
46	0 ~ +2,90	max. 2000
55, 60, 65, 70, 75, 80, 85, 90, 95, 100	0 ~ +2,50	max. 3000
68	0 ~ +4,00	max. 2000
88	0 ~ +5,20	max. 2000
110, 120, 130, 140, 150	0 ~ +2,50	max. 3000
180, 200	0 ~ +3,00	max. 3000
23	0 ~ +1,40	max. 2000
27	0 ~ +1,60	max. 2000
28	0 ~ +1,70	max. 2000
32	0 ~ +1,90	max. 2000
35, 40, 45, 50	0 ~ +1,60	max. 3000
38	0 ~ +2,30	max. 2000
44	0 ~ +2,6	max. 2000
46	0 ~ +2,90	max. 2000
55, 60, 65, 70, 75, 80, 85, 90, 95, 100	0 ~ +2,50	max. 3000
68	0 ~ +4,00	max. 2000



88	0 ~ +5,20	max. 2000
110, 120, 130, 140, 150	0 ~ +2,50	max. 3000
180, 200	0 ~ +3,00	max. 3000
38	0 ~ +2,30	max. 2000
44	0 ~ +2,6	max. 2000
46	0 ~ +2,90	max. 2000
55, 60, 65, 70, 75, 80, 85, 90, 95, 100	0 ~ +2,50	max. 3000
68	0 ~ +4,00	max. 2000
88	0 ~ +5,20	max. 2000
110, 120, 130, 140, 150	0 ~ +2,50	max. 3000
180, 200	0 ~ +3,00	max. 3000

Nicht aufgeführte Abmessungen auf Anfrage